



■ ■ ■ features + benefits

HIGH PERFORMANCE LED BOARDS	<ul style="list-style-type: none"> • Provides increased lumen output while decreasing overall wattage consumption • Multiple colour temperatures available: 3000K, 4000K or 5000K • Lumen packages available from 9996lm – 12,374lm and efficacy up to 134 lm/W
EMERGENCY OPERATION	<ul style="list-style-type: none"> • Minimum of 90 minutes as an option
IP66 RATED	<ul style="list-style-type: none"> • For installation in wet location and dust filled environments • Suitable for washdown areas with high psi
LIGHT WEIGHT DESIGN	<ul style="list-style-type: none"> • Just 5lbs, tool-less easy to install by one person • Hanging clips for hands-free wiring
9 DIFFERENT MOUNTING SYSTEMS	<ul style="list-style-type: none"> • Surface mount standard, aviation cable (AC), single & double pendants (SPK, DPK), chain hang standard, trunion mount (TM), junction mount (JM), magnetic mount (MM) and Pivot Mount (PV)
EXPECTED LED LIFE	<ul style="list-style-type: none"> • L85 rated > 60,000 hours
0-10V DIMMING STANDARD	<ul style="list-style-type: none"> • Compatible with most dimming systems
SANITATION LISTED	<ul style="list-style-type: none"> • Suitable for installation in food preparation areas • Conforms to ANSI/NSF Std No.2