



## ■ ■ ■ features + benefits

|  |  |
|--|--|
| HAZARDOUS LOCATION                     | <ul style="list-style-type: none"> <li>• Class I Division 2, Groups A, B, C and D; Group II, Zone 1 &amp; Zone 2; Zone 21 &amp; 22.</li> </ul>   |
| CAST ALUMINUM HOUSING                  | <ul style="list-style-type: none"> <li>• Heavy-duty housing made of a copper-free aluminum and corrosion resistant casting.</li> </ul>   |
| 4MM THICK TEMPERED GLASS LENS          | <ul style="list-style-type: none"> <li>• Shock and vibration resistant</li> <li>• IK09 impact resistant</li> </ul>   |
| HIGH PERFORMANCE                       | <ul style="list-style-type: none"> <li>• 3,132 lm - 21,313 lm</li> <li>• Up to 118 lm/W.</li> <li>• From 30W up to 180W.</li> <li>• L70 (hrs) rated &gt; 54,000.</li> </ul>  |
| IP67 RATED                             | <ul style="list-style-type: none"> <li>• Dust tight and protected against the effects of immersion in water to depth between 15 cm and 1 meter.</li> <li>• Ideal for heavy industry, mining, refineries, chemical industry, coastal marine facilities and corrosive applications.</li> </ul> |
| ADJUSTABLE MOUNTING BRACKET            | <ul style="list-style-type: none"> <li>• Standard mounting comes with a 3mm thick steel mounting</li> <li>• Aimable at 135° on both sides in 22.5° increments</li> </ul>   |
| OPERATING TEMPERATURE OF -40°C TO 50°C | <ul style="list-style-type: none"> <li>• Suitable for applications with various temperatures</li> </ul>  |
| STANDARD DIMMING                       | <ul style="list-style-type: none"> <li>• 0 - 10V dimming to 10% is standard. Compatible with most dimming systems.</li> </ul>  |